

NOTES:

- 1. ALL WATER SERVICE INSTALLATIONS INCLUDE METER BOX AND MUST BE MARKED WITH A 3" STAMPED "W" ON FACE OF CURB.
- 2. MINIMUM 1" WATER SERVICE WITH 1" CORPORATION STOP, FORD. MUELLER OR JONES, STANDARD I P THREADS X PACK JOINT (AWWA) MUELLER P15008-FORD F1001-4. ALL BRASS FITTING AND CORPORATION COUNTER CLOCKWISE STOP SHALL BE LEAD FREE.
- 3. ALL WATER SERVICE SHALL HAVE A HAND TAMPED SAND BEDDING 6" BENEATH THE TUBING AND SHALL HAVE 12" MINIMUM CLEARANCE ON EACH SIDE AND 12" MIN. SAND COVER.
- 4. ALL WATER SERVICE SHALL BE POLYETHYLENE CTS SDR 9 (ASTM 2666) TUBING. ALL TUBING CONNECTIONS SHALL BE COMPRESSION TYPE: FORD, "PACK JOINT" OR APPROVED EQUAL.
- 5. WATER METER BOX SHALL BE PRE CORE CHRISTY B-36 FIBERLYTE (CHRISTY OR APPROVED EQUAL) TRAFFIC LID, SUBJECT TO VEHICLE TRAFFIC AND WITH METER READING DOOR AND PREDRILLED HOLE FOR METER READING ERT.
- 6. A MINIMUM SEPARATION OF 1'-0" BETWEEN WATER SERVICES REQUIRED ON COMMON TRENCH WITH MULTIPLE SERVICES TO BE INSTALLED MINIMUM 6" CLEARANCE BETWEEN TRENCH WALL & WATER SERVICE.
- 7. ALL TUBING TO FITTING CONNECTIONS SHALL INCLUDE STAINLESS STEEL INSERTS.
- 8. ALL SAND BACK FILL MATERIAL SHALL HAVE A MINIMUM SE=30 AND COMPACTED TO 90% RELATIVE COMPACTION.
- 9. WATER METER SIZES APPROVED BY CITY OF HOLLISTER ARE: APPROVED SIZES
- %", ¾", 1", 2", 4", 6", 8" AND 10"
- 10. GATE VALVE SHALL BE FORD, MULLER AND JONES OR APPROVED EQUAL.
- 11. INSTALL INSULATED STRANDED WIRE GAUGE #10 TO ALL WATER SERVICES.
- 12. WATER METER RADIO READ LID SHALL COMPLY WITH CITY OF HOLLISTER STANDARDS..
- 13. NO WATER SERVICE IN FIRE HYDRANT TRENCH ALLOWED.
- 14. NO WATER METER BOX INSTALL ON DRAINAGE SWALE.

WATER SERVICE			
DRAWN BY: LOUIE C. GUEVARA REVIEWED BY: DAVID RUBCIC \ REVISED: APRIL, 2013	APPROVED: AOUI	7-16-13	STANDARD PLAN
CITY OF HOLLISTER Engineering department	CITY ENGINEER: RUDI GOLNIK LIC. NO. 39570 EXP. DATE: 12-31-2013	DATE	SHEET 1 OF 3